NEW PRODUCT | PRODUCT NAME

	PRODUCT DETAILS		
DESCRIPTION.	AP-66T, shade pocket w/ tile lip, 6"x6"x10', WHT	AP-66, shade pocket, 6"x6"x10', WHT	AP-66e, pocket endplate, 6"x6",WHT
CODE.	RCCP-6001-075305	RCCP-6002-075305	RCCP-6100-075000
PACK SIZE.	2 0 Piece	2 0 Piece	50 100 Piece
PRICE.			
COLOUR / FINISH.	White	White	White
LENGTH.	10 ft.	10 ft.	n/a
IMAGE.			
USE WITH.	Bottom closures (RCBC2x, RCBC3x, RCBC5x) Endplate (RCCP-6100-075000)	Bottom closures (RCBC2x, RCBC3x, and RCBC5x) Endplate (RCCP-6100-075000)	Pockets (RCCP-6001-xxx305 and RCCP-6002-xxx305)
AVAILABLE.	6/3/21	6/3/21	6/3/21

FEATURES & BENEFITS

PRODUCTION / INSTALLATION FEATURES

- Member of the AR Series of architectural recessed pockets
- Simplified design provides versatility for use with Rollease Acmeda shading systems or others
- External dimensions are 6in x 6in x 10ft (tile lip is 0.75in)
- Available with and without a ceiling tile lip for drop-ceiling applications
- Competitive pricing
- Inventory is stocked in the US, reducing delivery times
- Easy installation use self-tapping mounting screws to fasten to overhead supports directly through the top of the pocket (see Reference & Installation Guide)
- Aluminum composition retains structural integrity while allowing on-site cutting
- Extrusions are 10' in length to allow for easier transportation navigating job sites (stairwells, elevators, etc.)

Endplate

- Rotationally symmetric for ease of fabrication
- Compatible with standard hardware (#6 flat head screw, Catalog #: RCEPS100xx)

FUNCTIONAL BENEFITS

AESTHETIC FEATURES



NEW PRODUCT | PRODUCT NAME

 Simplified internal design to work easily with Rollease Acmeda shading systems as well as other systems. External dimensions are symmetrical at 6" x 6" for easier installation measurements Available with or without ceiling tile lip Maximum roll-up diameter: Single shade: 5.19" Dual shades: 3.03" 	 Offered in powder-coated White Use with colored Endplate and Bottom Closures for a clean look.
---	---

To request a sample please contact your Account Manager or our Customer Service Department on 203 964 1573 Page 2 of 2 | Release Date: 03/06/2021

