Regulatory Compliance







Do not dispose of in general waste. Please recycle batteries and damaged electrical products appropriately.

Specifications:

Model	AUTOMATE Rechargeable Battery Pack - 5V	Rolleas
Model #	MT03-0305-069003	essenti
Input Voltage	5 VDC	UN38.3
Input Current	2 A	UL 2595
Typical Voltage	12 VDC	CSA C22
Nominal Voltage	10.8 V	
Nominal Capacity:	2.6 Ah	
Charging time	≈ 7 Hours	
IP Rating	N/A	
Limit Switch Type	N/A	
Radio Frequency	N/A	
Battery Size/Type	1-1/4"×1-1/4"×10" / Li-ion Rechargeable	
Temp Working	32°F to 140°F (0°C to 60°C)	
Class	N/A	

Rollease Acmeda declares that this equipment is compliance with the essential requirements and is tested to comply with:

UN38.3	UN Transport Test and Criteria for Lithium Batteries	
UL 2595, CSA C22.2 No. 0.23	General Requirements for Battery-Powered Appliances	

Battery Safety Statement

Product safety is considered integral to Rollease Acmeda's product offering.

As such, all products containing lithium-ion batteries are manufactured, tested and certified to stringent standards.

Testing is conducted to cover all aspects of the UN Model Regulations, Manual of Test and Criteria, Part III, subsection 38.3, including:

- Altitude Simulation
- Thermal Test
- Vibration
- Shock
- External Short Circuit
- Impact / Crush
- Overcharge
- Forced Discharge

Additionally, all battery products assemblies utilize an integrated charge management circuit which protects against over or under charging. This circuit also enables individual cell balancing which ensures the longevity and integrity of the entire battery pack.

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment

