

AUTOMATE™ LI-ION

WIREFREE MOTORS

- Leveling control
- Simple limit setting and adjustment
- Favourite position
- 3 operational speed settings available
- 2 way RF communication
- Rechargeable built in Li-ion battery
- Optional solar powered charger
- Over 500 up / down operations on a single charge (based on recommended maximum shade sizes)
- ARC™ protocol featuring efficient programming, battery power conservation and bi-directional communication



Li-ion 0.2 Nm



Li-ion 1.1 Nm



Li-ion Q2.0 Nm



Li-ion 3.0 Nm
Li-ion Q3 Nm
Li-ion Q10 Nm



AUTOMATE™ LI-ION

FEATURES



Electronic
Limit Switch



Battery
Powered



Favorite
Position



Leveling
Control



433MHz
Bi-directional



Adjustable
Speed



Quiet
Operation

APPLICATIONS



Roller Shade



Roman
Shades



Wood Blind*

*Lift and tilt
operation
Li-ion 3.0 only



Solar Panel



AC Charger

CHARGING OPTIONS

SPECIFICATIONS

	Voltage	Torque	Speed	Motor Length
Li-ion 0.2	12	0.2Nm	80rpm (Adj. to 60 or 40)	17.75"
Li-ion SW1.1	12	1.1Nm	40rpm	17.56"
Li-ion 1.1	12	1.1Nm	40rpm (Adj. to 30 or 20)	17.50"
Li-ion Q2.0	12	2Nm	28rpm (Adj. to 24 or 20)	25.80"
Li-ion 3.0	12	3.0Nm	28rpm (Adj. to 24 or 20)	25.54"
Li-ion Q3.0	12	3.0Nm	28rpm (Adj. to 24 or 20)	32.04"
Li-ion Q10	12	10.0Nm	9rpm (Adj. to 8 or 6)	32.04"



rolleaseacmeda.com

USA | AUSTRALIA | EUROPE

© Rollease Acmeda Group