

X-Weave Zero

Exterior Solar Screen



TEXTSTYLE

X-Weave Zero


X-Weave Zero is a heavy-duty fire-retardant solar screen fabric with 0% openness for use in exterior and interior spaces. Its 100% view blocking design provides enhanced privacy, solar protection, and resistance to rain and insects. It's wide width of 126 inches, extended color palette of 11 colors, and strong tensile strength makes X-Weave's durability and versatility its strongest characteristics.

Mix opacities with X-Weave 5% or 10% depending on your viewing needs. Pair X-Weave Zero with Zipscreen Exterior system to protect yourself from the elements and expand your living space by bringing the outdoors inside.

Features

- 100% view blocking for total privacy
- For Exterior and Interior use
- Insect and Rain Resistant
- 126" wide
- Matching color pallet to X-Weave 5% and 10%
- Comes with EPD, HPD, GREENGUARD Gold, OEKO-TEX Standard 100
- NFPA 701 Fire Classification
- 10 Year Warranty

Colors




WHITE



SUNRISE




SAND



FOSSIL




STONE GRAY




GRAPHITE



SLATE



SUNSET



MAHOGANY



OBSIDIAN



ONYX

X-Weave Zero

Exterior Solar Screen



Specifications

	0%
Composition	30% Polyester, 70% PVC
Openness Factor	Approx. 0%
Weight	19.17 oz/yd ² (650g/m ²)
Thickness	0.033in (.85mm)
Light Fastness	≥ 5 (Blue wool scale)
Average length	22yd/roll (20m)
Width	126" (3m)
Cutting	knife, Crush, Ultrasonic
Welding	248°F (120°C) to 284°F (140°C), test first
Railroadable	Yes, for side tensioned systems only.
Cleaning	Wipe clean with warm soapy water and damp cloth
Environmental Standards	GREENGUARD Gold, OEKO-TEX Standard 100 & ISO 14001
Fungal/Bacterial Resistance	ASTM G21, ASTM E2149
Tensile Strength	Warp: 3720 N/5cm Weft: 1230 N/5cm
Tearing Strength	Warp: 650 N Weft: 126 N
Fire Classifications	NFPA 701

X-Weave Zero

Exterior Solar Screen



Thermal and Optical Factors

COLOR		THERMAL FACTORS			OPTICAL FACTORS		FABRIC & GLASS	
		Rs	As	Ts	Rv	Tv	SHGC% Improvements	SHGC
0%	White	76	14	10	84	7	69	0.14
	Sunrise	59	35	6	65	4	60	0.19
	Fossil	24	75	1	25	1	43	0.32
	Graphite	6	94	0	7	0	36	0.34
	Mahogany	5	95	0	6	0	35	0.35
	Obsidian	5	95	0	5	0	35	0.35
	Onyx	4	96	0	4	0	34	0.35
	Sand	57	32	11	59	7	57	0.22
	Slate	9	91	0	10	0	37	0.33
	Stone Gray	32	66	2	34	1	47	0.27
	Sunset	7	93	0	8	0	36	0.34



FR



ENERGY
SAVING



REACH
COMPLIANT



RoHS
COMPLIANT



INSECT
RESISTANT



PRINTABLE